



NORMco pump & power

made in the USA

6" x 3" 173HP NORMCO PUMP DIESEL - DRIVEN CENTRIFUGAL PUMP PACKAGE

PUMP SPECIFICATIONS

Model	PP63C17
Size	6" X 3"
Impeller	17"
Max Flow	1200 gpm
Max Head	520'
Solids Size	.76"

FEATURES AND BENEFITS

- Run-dry capable
- Enviromentally safe priming system
- Auto-start controls
- Instrument Compatibility: High/low level floats, transducers
- Automation ready

MOTOR SPECIFICATIONS

Engine Type	6068, 6-Cylinder Diesel
Displacement	415 cu in
Fuel Consumption	7.6 gph
Rated HP	173HP
Emission Specs	Tier 3

PACKAGE SPECIFICATIONS

Fuel Capacity	185 gallons
Control Panel	Controls Inc.
Operating Speed (Min./ Max)	1,300/2,200 rpm
Weight (Dry/Wet)	5,500/7,000 lbs
Trailer Brakes	Electric

PRIMING SYSTEM

Priming System	Belt driven diaphragm style pump
Air Removal Capacity	50 cfm
Priming Chamber	Positive sealing air separation
Discharge Check Valve	Swing style
Run Dry System	Oil-lubricated mech. seal allows pump to run dry without damage

MATERIALS OF CONSTRUCTION


Impeller	CA6NM Stainless Steel
Shaft	17-4 PH Stainless Steel
Volute	Ductile Iron ASTM A536 65-45-12
Wear Ring	ASTM A48 Class 40 Gray Iron
Suction Cover	Ductile Iron ASTM A536 65-45-12
Bracket	Ductile Iron ASTM A536 65-45-12
Mechanical Seal	Silicon Carbide rotating and Tungsten Carbide stationary

NORMCO PUMP DIESEL - DRIVEN CENTRIFUGAL PUMP PACKAGE
6" x 3" 173HP

NORMco
pump & power

made in the USA

PUMP DIMENSIONS



PUMP CURVE

